

Adapter



Features

- ◆ Sourcelight Supplied Adapter which performance met with all the requirement of IEC standard.
- ◆ Compatible with RoHS.

Applications

- ◆ optical fiber communication system
- ◆ optical fiber access network
- ◆ optical fiber data transmission
- ◆ optical fiber CATV
- ◆ local area network (LAN)

Overview

Fiber optic connector adapter both ends can be inserted into different interface types: FC, SC, ST, LC, MTRJ, MPO, E2000, so widely used in optical fiber distribution frame and communication equipment.

Technical Specification

Type	LC / SC / FC / ST / MTRJ / MU / MPO SMA / DIN / E2000 / Hybrid Adapter
Application	PC / APC
Mode	Single Mode / Multi Mode
Sleeve	Zirconia Ceramic / Phosphor Bronze / NA
Adapter housing	Engineering Plastics / Metal
Insertion Loss	≤ 0.2 dB
IL variation after 500 connections	≤ 0.1 dB
IL variation during withdraw force test	≤ 0.2 dB
Tensile strength of welding	> 100N
Adapter housing color	Blue / Green / Beige / Metal / Black / Argentine
Environmental Temperature	- 40°C ~ + 75°C
Storage Temperature	- 45°C ~ + 85°C

Shenzhen Sourcelight Technology Co., Ltd

Sourcelight Technology reserves the right to make changes to or discontinue any optical link product or service identified in this document without notice in order to improve design and/or performance. If you have any question regarding this specification sheet, please contact our sales representative or send email to sales@sourcelight.com.cn